nobilia

Technical product descriptions

Worktops

I	Standard	
1)	**Material thickness**	38 mm
2)	**Substrate material**	Chipboard
3)	**Surface material**	Laminate (CPL / HPL)
4)	**Laminate thickness**	0.6 - 0.8 mm
5)	**Surface structure**	individual for each décor
6)	**Front edge type**	
	N-edge	The laminate panel is coated around both rounded front edges.
	Inserted N-edge	An inserted worktop piece that is coated around both rounded front edges.
	Décor edge (D-edge)	1.5 mm thick PP plastic lippings in worktop décor. All 90° outer corners are supplied in square design. Optional: rounded design with outer radius of 20 mm, inner corners with a radius of 30 mm. The PP edging is glued with waterproof PUR adhesive.
7)	**Coating of the underside**	Water-repellent, resin-soaked paper, joint between the bottom and top coating sealed.
8)	**Sealing**	must be applied on site for cut-outs and tongue and groove connections using a moisture-repelling agent. Worktop sealing tape is included in the fittings box.
9)	**Dimensions**	Max. length: 5,100 mm / max. width: 1,200 mm (N-edge), 1,170 mm (D-edge)

II	Worktops 25 mm	
1)	**Material thickness**	25 mm
2)	**Substrate material**	Chipboard
3)	**Surface material**	Laminate (CPL / HPL)
4)	**Laminate thickness**	0.6 mm both faces
5)	**Surface structure**	individual for each décor
6)	**Front edge type**	
	Décor edge	The worktops are coated with a 1.5 mm thick décor edge on the front and side. All 90° outer corners are supplied in square design. Optional: rounded design with outer radius of 20 mm, inner corners with a radius of 30 mm. The PP edging is glued with waterproof PUR adhesive.
7)	**Coating of the underside**	HPL / Counteracting paper
8)	**Sealing**	must be applied on site for cut-outs and tongue and groove connections using a moisture-repelling agent. Worktop sealing tape is included in the fittings box.
9)	**Dimensions**	Max. length: 3,400 mm / max. width: 1,170 mm

III	Slimline	
1)	**Material thickness**	16 mm
2)	**Substrate material**	HDF
3)	**Surface material**	Laminate (CPL / HPL)
4)	**Laminate thickness**	0.6 - 0.8 mm, both faces
5)	**Surface structure**	individual for each décor
6)	**Front edge type**	
	Décor edge	Worktops are laminated with a 1.5 mm thick décor edge all around. All 90° outer corners are supplied in square design. Optional: rounded design with outer radius of 20 mm, inner corners with a radius of 30 mm. The PP edging is glued with waterproof PUR adhesive.

Technical product descriptions

7)	**Coating of the underside**	CPL / HPL
8)	**Sealing**	must be applied on site for cut-outs and tongue and groove connections using a moisture-repelling agent. Worktop sealing tape is included in the fittings box.
9)	**Dimensions**	Max. length: 3,400 mm / max. width: 1,170 mm, 605 mm (Sakura design line)

IV	Xtra	
1)	**Material thickness**	38 mm
2)	**Substrate material**	Chipboard 27.4 mm
3)	**Functional layer**	HDF 9.4 mm
4)	**Surface material**	Laminate (HPL) with antibacterial and antiviral microPLUS® surface
5)	**Laminate thickness**	1.2 mm
6)	**Surface structure**	individual for each décor
7)	**Edge type**	
	Décor edge	1.5 mm thick PP plastic lippings in worktop décor. All 90° outer corners are supplied in square design. Optional: rounded design with outer radius of 20 mm, inner corners with a radius of 30 mm. The PP edging is glued with waterproof PUR adhesive.
8)	**Coating of the underside**	1 mm laminate
9)	**Sealing**	must be applied on site for cut-outs and tongue and groove connections using a moisture-repelling agent. An assembly set incl. sealant is supplied for flush mounted cut-outs. Worktop sealing tape is included in the fittings box.
10)	**Flush mounted cut-outs**	Cut-outs for flush mounting sinks and hot plates are prefabricated at the factory.
11)	**Dimensions**	Max. length: 4,000 mm / max. width: 1,170 mm (D-edge)

V	Console panel	
1)	**Material thickness**	100 mm
2)	**Substrate material**	Sandwich chipboard
3)	**Surface material**	Laminate (CPL / HPL)
4)	**Laminate thickness**	0.6 - 0.8 mm, both faces
5)	**Surface structure**	individual for each décor
6)	**Edge type**	
	Décor edge	1.5 mm thick PP edging all around
7)	**Coating of the underside**	Laminate (CPL / HPL)
8)	**Dimensions**	Minimum dimensions: 200 x 200 mm Maximum: 1,200 mm deep, 1,800 mm wide
9)	**Assembly**	50 % of the console panel must rest on the support panel. Built-in hot plates and sinks are not possible.

VI	Quartz	
1)	**Material thickness**	12 mm or 38 mm
2)	**Substrate material**	12 mm: Quartz composite (solid material) 38 mm: 12 mm quartz composite with wooden profile substructure (composite material)
3)	**Surface**	silk matt / décors according to sales manual
4)	**Edge type**	
	Décor edge	12mm: polished with double chamfer 38mm: mitred with chamfer
5)	**Dimensions**	Max. length: 3,000 mm / max. width: 1,200 mm
6)	**Cut-outs**	Cut-outs for sinks and hot plates are prefabricated at the factory

nobilia

Technical product descriptions

		Cut-outs are secured with a transport bridge, which must be removed on site. Transport bridge as of width and depth: 12 mm: Width > 700 mm and depth > 300 mm 38 mm: Width > 900 mm and depth > 300 mm
7)	**Assembly**	Subsequent processing of quartz on site is only possible with suitable tools. Personal protective equipment is required for subsequent processing of quartz on site (minimum requirement FFP2 respiratory mask).
VII	**Xtra Ceramic**	
1)	**Material thickness**	16 mm
2)	**Substrate material**	6 mm of solid ceramic on a 10 mm lightweight backing layer made of recycled PET
3)	**Surface**	ultra matt / décors according to sales manual
4)	**Edge type**	
	Décor edge	1.2 mm design edge
5)	**Dimensions**	Max. length: 3100 mm / max. width: 1,200 mm
6)	**Cut-outs**	Cut-outs for sinks and hot plates are prefabricated at the factory
7)	**Assembly**	Subsequent processing of Xtra Ceramic on site is only possible with suitable tools. Personal protective equipment is required for subsequent processing of Xtra Ceramic on site (minimum requirement FFP2 dust mask)
	Fronts	
1)	**Material thickness**	19 mm, 22 mm
2)	**Substrate material**	Chipboard, MDF
3)	**Surface material**	Melamine, lacquer, lacquered laminate, polymer film, laminate, aluminium framed glass, genuine wood veneer (living room furniture only)
4)	**Design**	range-based
5)	**Fastener**	at least two clipped hinges per front Glass cabinets “Air”: The hinges are fully hidden in the narrow aluminium profile
6)	**Cushioning**	All fronts are cushioned on the inner face with 2 mm thick plastic bumpers. Fronts of drawers and pull-outs equipped with push-to-open have no plastic buffer. All drawers, pull-outs and flaps are supplied standard with cushioned fittings. Hinged doors also come standard with additional cushioning integrated in the hinge.
7)	**Glazing**	Transparent float glass, etched matt glass, black glass, ribbed glass and program-specific glazing types (mostly TSG)
8)	**Edge design**	Thick edge mad of PP Program-specific: Lacquer or film applied vertically and/or horizontally around the edges Genuine wood veneer furniture (living room): Veneered edges
9)	**Special fronts**	
	Aluminium framed door	Aluminium frame with glass infill panel Frame colour matching the glass design
	Carcase material	
I	**Sides and construction shelves**	
1)	**Material thickness**	16 mm / 19 mm
2)	**Substrate material**	Chipboard
3)	**Surface material**	Direct coating on melamine resin basis
4)	**Surface colour**	Standard: white on the inside, outside in carcase colour Optionally for surcharge: Carcase interior décor in slate grey (only available together with carcase Exterior décor 194 Slate grey!) Exception: Both sides in carcase colour for glass WU or shelf units Wall unit bottom side: outside in carcase colour

nobilia®

Technical product descriptions

5)	**Edging**	Base unit: front: PP edging in carcase décor, top, bottom, rear: paper edging TU: front: PP edging in carcase décor, top, bottom, rear: paper edging WU: front: PP edging in carcase décor, top + bottom: PP thin edging in carcase décor, rear: paper edging

II	**Insertable shelves**	
1)	**Material thickness**	
	Wood	16 mm
	Glass	5 mm / 6 mm (folding/lifting unit) / 8 mm (glass cabinets / bathroom designs)
2)	**Load capacity (wood / glass)**	Maximum recommended load for wood and glass shelves: 50 kg/m²
3)	**Substrate material**	Chipboard / glass
4)	**Surface material**	Direct coating on melamine resin basis
5)	**Surface colour**	Standard: white shelf For glass wall units glass shelves; for shelf units in carcase colour
6)	**Edging**	front: PP edging, side/ rear edging paper edging and melamine edging
7)	**Shelf fastening**	Metal shelf supports
8)	**Adjustability of the shelves**	Grouped holes

III	**Back panel**	
1)	**Material thickness**	Thickness: 2.8 mm
2)	**Substrate material**	Hard fibre board (HDF, MDF)
3)	**Surface colour**	front: lacquered / printed / laminated; back: lacquered

IV	**Connection of the sides, shelves and back panel**	
1)	**Base unit**	Shelf and sides glued together with hardwood dowels (8x30 mm) as corner connectors
2)	**Wall unit**	Shelf and sides glued together with hardwood dowels (8x30 mm) as corner connectors
3)	**Tall unit**	Shelf and sides glued together with hardwood dowels (8x30 mm) as corner connectors
4)	**Back panel**	grooved 4-6 mm into carcase side, screwed to the base at the top and bottom for wall units with a width of 1,000 mm and more without a centre post, the back panel is divided by a rail guide

	Plinth	
1)	**Material thickness**	13 mm
2)	**Base and surface material**	a) MDF with melamine resin based direct coating with integrated sealing profile b) Water resistant plinth: Plastic hollow chamber profile incl. base seal c) Aluminium slatted plinth
3)	**Surface colour**	a) Design available in all carcase colours and various other décors b) Décor: F 114 Stainless steel appearance, F 049 Mirror décor, 058 Black, 061 Brushed steel reproduction c) Décor: F 114 Stainless steel appearance, F 058 Black, F 193 Alpine white
4)	**Dimensions**	
	Plinth height	70, 100, 150, 200 mm 20 mm in living segment Up to 28 mm in kitchen segment. However, not permitted in active kitchen areas (cooking, washing dishes, refrigerating)!
	Fixed lengths	2,200 mm, 3,350 mm / Exception for aluminium slatted plinth: 2,000 mm and 4,000 mm
5)	**Plinth assembly**	
	Floor sealing profile	Integrated sealing lip as floor connection Optional: attached U profile for flexible compensation of floor irregularities
	Plinth corner set	Hollow chamber profile

	Surrounding materials
I	**Upright panels / top shelves /light bottom shelves**

nobilia

Technical product descriptions

1)	**Material thickness**	10, 16, 25, 50 mm
2)	**Surface material**	10, 16, 25, 50 mm: Direct coating on melamine resin basis 10, 16 mm: available in lacquer, lacquered laminate Product group Living: Upright panels and light bottom shelves not available in genuine wood veneer design; top shelves are available in 10 mm genuine wood veneer design
3)	**Surface colour**	10, 16, 25, 50 mm: Surface colour acc. to sales manual available in carcase and worktop décor, partially also in front material as well as matt, supermatt, ultra matt, high gloss and ultra high gloss décor
4)	**Special design (bathroom/living)**	Lacquered laminate upright panels: 25 mm thick with rounded front edge incl. 21 mm outer radius; bevelled upright panels: 16 mm thick (all carcase colours and all front colours of the Easytouch 945 range) / top shelves: with 22.5 mm corner radius, matching front edge!

II	**Niche cladding in carcase and worktop décors**	
1)	**Material thickness**	16 mm
2)	**Substrate material**	Chipboard
3)	**Dimensions**	maximum width: 2580 mm, maximum height: 2030 mm (exception: Xtra décors, all HG décors, F 014 Stainless steel appearance, F 211 Bronze metallic colour, F 296 Yellow gold coloured, F 366 Black textured => max. height 1200 mm)
4)	**Surface colour**	Version in carcase, HG, worktop, Xtra worktop décors and in F 014 Stainless steel appearance, F 211 Bronze metallic colour, F 296 Yellow gold coloured
5)	**Direction of finish**	Horizontal

III	**Niche cladding with motifs**	
1)	**Material thickness**	16 mm
2)	**Substrate material**	Chipboard
3)	**Dimensions**	Niche cladding with digital print motif: max. width: 2,800 mm, max. height: 1,200 mm niche cladding with motif in 3D digital print: max. width: 2,800 mm, max. height: 1,200 mm niche cladding with motif in 3D texture: max. width: 2,040 mm, max. height: 2,770 mm
4)	**Surface colour**	Niche cladding with motif (NVM): coated on both sides, front side with digital print and lacquer finish, décors according to sales manual Niche cladding with motif in 3D texture (NVMDS): coated on both sides, front side with tactile texture, décors according to sales manual
5)	**Direction of finish**	NVMDS: vertical

IV	**Glass and mirror Niche cladding**	
1)	**Material thickness**	16 mm
2)	**Dimensions**	Height: 250 - 1,200 mm, width: 250 - 2,500 mm
3)	**Substrate material**	Chipboard (substrate): 12 mm safety glass (TSG): 4 mm
4)	**Surface colour**	Décors according to sales manual
5)	**Special considerations**	Profiling, notching and holes possible acc. to sales manual

V	**Quartz niche cladding**	
1)	**Material thickness**	12 mm
2)	**Dimensions**	Height: 301 - 563 mm, width: 250 - 3,000 mm (NVQ 54) height: 300 mm, width: 250 - 3,000 mm (NVQ) height: 700 mm, width: 600 mm, 900 mm or 1,000 mm (NVQ) height: 50 mm , width: 100 - 1,500 mm (WAQ)
3)	**Substrate material**	Quartz composite
4)	**Surface**	silk matt / décors according to sales manual
5)	**Edge**	Polished and chamfered on 3 sides
6)	**Special considerations**	Profiling, notching and holes possible acc. to sales manual. Assembly set containing silicone for sealing

VI	**Niche cladding made of Xtra Ceramic**	
1)	**Material thickness**	16 mm

nobilia®

Technical product descriptions

2)	**Dimensions**	Height: 301 - 559 mm, width: 250 - 3,100 mm (NVC 56) height 300 mm, width: 250 - 3,100 mm (NVC) height: 700 mm, width: 600 mm, 900 mm or 1,000 mm (NVC) height: 75 mm , width: 100 - 1,500 mm (WAC)
3)	**Substrate material**	6 mm of solid ceramic on a 10 mm lightweight backing layer made of recycled PET
4)	**Surface**	ultra matt / décors according to sales manual
5)	**Edge**	1.2 mm design edge
6)	**Special considerations**	Profiling, notching and holes possible acc. to sales manual. Assembly set containing silicone for sealing

VII	**Accessories**	
1)	**Plug-in wall shelf**	
	Material	Chipboard, direct coating on melamine resin basis, PP edging all around
	Material thickness	a) 16 mm / also available with bevelled front edge
		b) 25 mm
	Dimensions	a) Depth: 150 mm
		b) Depth: 255 mm
	Load-bearing capacity	a) 6 kg per pair of supports
		b) 12 kg per pair of supports
2)	**Wall shelves with shelf holders**	
	Material	Chipboard, direct coating on melamine resin basis, PP edging all around TSG glass Bevelled wall shelf with bevelled front edge
	Material thickness	16 mm, 25 mm, 50 mm Glass = 8 mm Bevelled wall shelf = 16 mm
	Load-bearing capacity	16 kg per pair of supports
3)	**Wall shelves with console support**	
	Material	Chipboard, direct coating on melamine resin basis, PP edging all around
	Material thickness	16 mm, 25 mm
	Load-bearing capacity	16 kg per pair of supports
4)	**Sliding doors system**	
	Material	
	Sliding doors	Aluminium frame in 014 Stainless steel appearance or 10 Black Décor panels coated on both faces, mirror with safety film on back white, grey glass (TSG)
	Runner	1-, 2-, 3-track top and bottom runners in stainless steel appearance or black
	Dimensions	
	Sliding doors	Height: 700 - 2,600 mm, width: 500 - 1200 mm Sliding doors without inlays: F 402 EI Havana reproduction, F 405 EI Sierra reproduction, F 889 Slate grey concrete and F 892 Grey concrete only available up to a max. height of 2,000 mm
	Runner	Height: Bottom runner 6 mm, top runner 40 mm, width: max. 5,000 mm Installation depth: 1-track 40mm, 2-track 79 mm, 3-track 117 mm

nobilia®

Technical product descriptions

Fittings

I	**Hinges**	
1)	**Type / Model**	Sensys hinge with integrated cushioning
2)	**Material**	Metal
3)	**Fastening of the mounting plate**	bolted twice with expansion sleeve
4)	**Fastening of the clipped hinge**	Clipped connection, assembly and disassembly on the mounting plate without tools
5)	**Opening angle**	
	Standard	110°
	Hinged door for internal drawer	165°
	Corner units	165°
	Diagonal types	30° / 95°
	Limiters	Optional opening angle limiter of 85° for corner solutions or for wall mounting
6)	**Adjustability**	Depth adjustment: - 2 / + 3 mm
		Height adjustment: ± 2 mm
		Side adjustment: ± 2 mm
7)	**Number per door**	min. 2 hinges per door

II	**Drawers / front pull-outs**	
1)	**Material**	Steel frame, steel rear panel or wooden rear panel for all vanity units and variable waste separation systems, 16 mm chipboard shelf
2)	**Construction**	Metal
3)	**Connection front / frame**	Tool-free installation of front panels; unlocking of front panels using screwdriver.
		adapter dowelled into the front panel
		Adjustability: Side adjustment ± 1 mm; height adjustment ± 2 mm
		Front panel angle adjustment using adjustment option in the back panel: -1 mm / + 3 mm
4)	**Pull-out cushioning**	Integrated hydraulic cushioning
5)	**optional: Push-to-open opening mechanism** **optional: Opening support mechanism Libero 3.0**	Push-to-open opening mechanism for handleless designs: Mechanical opening support mechanism for drawers, pull-outs, larder units Junior and side pull-outs. Handleless opening, cushioned closing. Opening support mechanism "Libero 3.0": Operation by foot using laser sensor and / or voice control for waste separation systems: Separato-K, Flex 33, Flex 21, Frame, Syncro and Euro Cargo

III	**Drawers / front pull-outs: Bearings**				
1)	**Type**	Roller bearings with load dispersion roller			
2)	**Model**	Full pull-out (drawer / pull-out / low frame)			
3)	**Material**	Steel			
4)	**System load**	Drawers: of all widths and depths up to 30 kg. Pull-outs:			
		Width:	≤ 60 cm	> 60 to ≤ 90 cm	>90 to ≤ 100 cm	> 100 cm
		Depth:				
		30 cm	30 kg	30 kg	30 kg	30 kg
		40 cm	30 kg	40 kg	40 kg	40 kg
		50 cm	30 kg	45 kg	55 kg	55 kg
5)	**Protection against pulling out**	Catch mechanism on rail			

IV	**Additional functional fittings**	
1)	**Larder unit**	Full pull-out with cushioned opening and closing, 80 kg additional load
2)	**Carousel**	360° rotation, height-adjustable, 20 kg additional load per shelf
3)	**FurnSpin**	For two defined end positions: 0° and 180°, 20 kg added load per shelf

nobilia

Technical product descriptions

4)	**Flap door fittings**	Flap door lift fittings with 112°/120° opening angle
		Flap door wall units with height of 360 mm, 100° opening angle
		Swivel flap doors with 75° opening angle
	Servo drive	Electric motor Servo Drive for wall units with swivel flap doors or folding/lifting doors
5)	**DSA side pull-outs**	Full pull-out with cushioning, load per shelf 10 kg
6)	**Corner unit rotary shelves**	Semi-circular rotary shelves, optional on left and right; 15 kg additional load per shelf
7)	**eTouch opening mechanism**	Electrical opening support mechanism for handleless designs of larder units HA* and Cargo tall units HC* using front sensor
8)	**Easys opening mechanism**	Electromechanical opening system for opening integrated fridges/freezers using a drive unit installed in the construction shelf. Only available for appliance housing units marked accordingly.
9)	**Lemans pull-out**	Half corner unit with swivel pull-out, additional load 25 kg per tablar shelf

Unit assembly

I	**Wall units**	
1)	**Material suspension brackets**	Metal
2)	**Number of suspension brackets per unit**	min. 2 pieces centre suspension concealed for folding-lifting wall units and shelf units upwards of 1,000 mm width
3)	**Type of adjustability**	Height adjustment - 7 / +10 mm Depth adjustment - 1 / +11 mm Side adjustment +/- 2.5 mm
4)	**Method for fastening in the carcase**	4 metal pins in carcase side with two special screws fastened in a hidden position behind the back panel. Cover caps are included in the scope of delivery
5)	**Fastening on the building wall**	Metal mounting rails
		Integrated tool-free guard against accidental unhooking
		Freely suspended wall units and all flap door wall units must be secured against slipping or unhooking by means of brackets
6)	**Load capacity**	The maximum load for wall units is 75 kg, with the individual shelves carrying a maximum load of 16 kg
7)	**Lighting**	Lighted shelf as wall unit bottom shelf with integrated lighting (MP-LA)
		Various lighting fixtures integrated in the top and bottom shelf
		Wall unit bottom shelf with attached profile strip in stainless steel appearance for opening original fronts without a handle, with integrated LED light strip (MP-WOGL)

II	**BU island solution**	
1)	**Tilt protection**	Island tilt protection using additional metal foot

III	**Base units for bathroom and living room designs**	
1)	**Material suspension brackets**	Heavy-duty suspension brackets
2)	**Number of suspension brackets per unit**	2 heavy-duty suspension brackets
3)	**Type of adjustability**	Adjustment option behind back panel (not visible): Back panel offset 23.5 mm: Depth adjustment - 2 mm / + 11 mm Back panel offset 38.5 mm: Depth adjustment - 6 mm / + 7 mm Height adjustment +/- 10 mm
4)	**Method for fastening in the carcase**	4 press-in dowels in the carcase side
5)	**Fastening in the building wall**	Mounting plate with integrated metal safety brackets. The heavy-duty suspension bracket ensures secure mounting in honeycomb brick, sand-lime brick and concrete.
6)	**Load capacity**	The maximum load for bathroom base units is 75 kg, with the individual shelves carrying a maximum load of 16 kg
7)	**Plinth designs**	For designs standing on the floor with 20 mm plinth foot
		Height adjustment - 2 / + 8 mm (incl. 5 mm high adapter)
8)	**Special types**	Mirrored cabinets

Carcase dimensions

nobilia

Technical product descriptions

I	Kitchen furniture	
1)	**Base units**	
	Mini	Carcase height: 576 mm; carcase depth: 560 mm or optionally 460 mm side depth: carcase depth + front thickness
	Standard	Carcase height: 720 mm; carcase depth: 560 mm or optionally 460 mm side depth: carcase depth + front thickness
	XL	Carcase height: 792 mm; carcase depth: 560 mm or optionally 460 mm side depth: carcase depth + front thickness
	Maxi	Carcase height: 864 mm; carcase depth: 560 mm or optionally 460 mm side depth: carcase depth + front thickness
	Common special heights	Carcase heights: 288 mm; 360 mm; 432 mm
2)	**Wall units**	
	Wall unit height - 36	Carcase height: 360 mm; carcase depth: 350mm side depth: carcase depth + front thickness
	Wall unit height - 58	Carcase height: 576mm; carcase depth: 350mm side depth: carcase depth + front thickness
	Wall unit height 1	Carcase height: 720 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Wall unit height 2	Carcase height: 792 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Wall unit height 3	Carcase height: 864 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Wall unit height - 130	Carcase height: 1,296 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
3)	**Sideboards**	
	Sideboard height - 36	Carcase height: 360 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Sideboard height - 58	Carcase height: 576mm; carcase depth: 350mm side depth: carcase depth + front thickness
	Sideboard height 1	Carcase height: 720 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Sideboard height 2	Carcase height: 792 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Sideboard height 3	Carcase height: 864 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Sideboard height - 130	Carcase height: 1,296 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
4)	**Dresser units**	
	Standard	Carcase height: 754 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Dresser unit height 1	Carcase height: 1258 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Dresser unit height 2	Carcase height: 1330 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
	Dresser unit height 3	Carcase height: 1,402 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
5)	**Highboards**	
	Standard	Carcase height: 1,512 mm; carcase depth: 560 mm / 460 mm side depth: carcase depth + front thickness
	XL	Carcase height: 1,584 mm; carcase depth: 560 mm / 460 mm side depth: carcase depth + front thickness
6)	**Tall units**	
	Tall unit height 1	Carcase height: 2,016 mm; carcase depth: 560 mm side depth: carcase depth + front thickness
	Tall unit height 1 XL	Carcase height: 2,088 mm; carcase depth: 560 mm side depth: carcase depth + front thickness
	Tall unit height 2	Carcase height: 2,088 mm; carcase depth: 560 mm side depth: carcase depth + front thickness
	Tall unit height 2 XL	Carcase height: 2,160 mm; carcase depth: 560 mm side depth: carcase depth + front thickness
	Tall unit height 3	Carcase height: 2,160 mm; carcase depth: 560 mm side depth: carcase depth + front thickness

Technical product descriptions

	Tall unit height 3 XL	Carcase height: 2,232 mm; carcase depth: 560 mm side depth: carcase depth + front thickness

	Bathroom and living room furniture	
1)	**Base units**	Carcase heights: 216 / 288 / 360 / 432 / 504 / 576 / 603 / 630 mm; carcase depth: 461 mm side depth: carcase depth + front thickness
2)	**Sideboard & Midi units**	Carcase heights: 720 / 864 / 1,152 / 1,247 / 1,296 / 1,584 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
3)	**Bathroom - Mirrored cabinets**	Carcase height: 720 mm / carcase depth: 202 mm Carcase height: 1296 mm / carcase depth: 350 mm side depth: carcase depth + front thickness
4)	**Glass cabinets for living room designs**	Carcase heights: 1296 / 2016 mm; carcase depth: 350 mm side depth: carcase depth + front thickness
5)	**Highboards and tall units for living room designs**	Carcase heights: 1296 / 2016 mm; carcase depth: 350 mm side depth: carcase depth + front thickness

	Small terminology guide	
1)	**Laminate / HPL (High Pressure Laminate) or CPL (Continuous Pressure Laminate)**	Surface coating consisting of several décor, core and protective layers, thickness of 0.3 to 1 mm intended to create high-quality kitchen surfaces with high load bearing capacities suitable for their intended application
2)	**Direct coating**	Melamine-soaked décor paper used to create a high-quality décor surface
3)	**Chipboard**	Wooden material board made of chips and added glue
4)	**Real wood**	Solid wood or veneered wood composite
5)	**MDF (Medium density fibre board)**	Fibre board of medium density, made of wooden fibres and added glue
6)	**HDF (High density fibre board)**	Fibre board of high density, made of wooden fibres and added glue
7)	**System load**	System load calculated from the empty weight of the system (incl. front) plus additional load
8)	**Full pull-out**	The drawer / front pull-out can be pulled out of the unit up to the full, usable depth and even the rear section is accessible from the top
9)	**DIN / EN**	German standardisation institute (DIN) / European standard (EN)
		defines the requirements and properties of materials and finished products
10)	**PP**	Polypropylene
11)	**Clipped hinge**	Hinge is clipped onto the mounting plate without tools
12)	**Lacquered laminate**	Lacquered PET foil
13)	**microPLUS®**	Surface with antibacterial and antiviral effect made by Pfleiderer for all 38 mm Xtra worktops
14)	**TSG**	Tempered safety glass: Toughened glass, no subsequent processing possible
17)	**bevelled**	slanted profile